

FIBER BLOWERS

GMP'S TOP-OF-THE-LINE EQUIPMENT



	GENTLE AIR	WHISPER	AIRSTREAM	HURRICANE	JETSTREAM®	TORNADO
CABLE DIAMETER	1-3mm (.0039-.118")	3-8.5mm (.11-.33")	2.5-11mm (.10-.43")	2.5-14mm (.16-.79"	4-20mm (.16-.79")***	6-32mm (.24-1.26")*
TUBE SIZE (O.D.)	4 to 7mm (0.158 to 0.275")	4-18mm (1.5-.63")	5-18mm (.20-.71")	5 - 25mm (.20 - .98")	10 - 50mm O.D. (.75 - 1.50" SDR)	12-63mm O.D. (.75-2.00" SDR)
FLAT DROP COMPATIBLE	No	Yes with optional kit	Yes	No	No	No
EABF® COMPATIBLE	No	No	No	No	No	No
CABLE SPEED	0 - 300 ft/min (0 - 90 m/min)	0 - 300 ft/min (0 - 90 m/min)	0 - 262 ft/min (0 - 80m/min)	0 - 280 ft/min (0 - 85m/min)	0 - 280 ft/min (0 - 85m/min)	0 - 300 ft/min (0 - 90 m/min)
MAX AIR PRESSURE/VOLUME	220 psi (15 bar) 35 cfm (1m ³ /min)	220 psi (15 bar) 35 cfm (1m ³ /min)	220 psi (15 bar) 35 cfm (1m ³ /min)	220 psi (15 bar) 150-450 cfm (12m ³ /min)	220 psi (15 bar) 150-450 cfm (12m ³ /min)**	175 psi (12 bar) 150-450 cfm (4-12m ³ /min)**
DRIVE	Driver Roller	Driver Roller	Belts	Belts	Belts	Belts
CABLE SAFETY	Friction Torque Control	Torque Control via Drill	Electronic Torque Control	Electronic Torque Control	Hydraulic Pressure Sensing	Hydraulic Pressure Sensing
POWER	Varied Speed Drill	Varied Speed Drill	110/220 VAC	110/220 VAC	Gas/Hydraulic	Gas/Hydraulic
LENGTH	9.7" (246mm)	9.7" (246mm)	18.1" (460mm)	21.6" (620mm)	24.5" (620mm)	42" (1070mm)
WIDTH	8.1" (206mm)	8.1" (206mm)	11.8" (300mm)	12.2" (484mm)	19" (484mm)	27" (690mm)
HEIGHT	8.5" (216mm)	8.5" (216mm)	10.6" (270mm)	13.8" (233mm)	9.2" (233mm)	48.5" (1230mm)
WEIGHT	12 lbs. (5.4kg)	12 lbs. (5.4kg)	33 lbs. (15kg)	53 lbs. (31kg)	68 lbs. (31kg)	155 lbs. (70kg)
OPTIONS	Own it!	Own it!	Rent, lease, or own	Rent, lease, or own	Rent, lease, or own	Rent, lease, or own

* MicroDuct (10 & 12mm O.D.) blowing available with add-on kit.

** Airflow required is duct size dependent.

*** 4-6mm fiber possible with dedicated bet.

CONTACT US TO GET STARTED.

WWW.MYMILLENNIUM.US | 866.287.7830 | INFO@MTPLLC.US